



喷射宽度 [B] p=3 bar

	H	
	250 mm	500 mm
664.721- 664.921	100	200
664.961- 665.121	115	210
664.722- 664.962	150	300
665.042- 665.202	160	310
664.723- 664.963	220	440
664.983- 665.123	250	490
664.724- 664.964	330	630
665.044- 665.124	340	640



订货号				材料号			E ∅ [mm]	V̇ [l/min]								
型号				16	17	30		p [bar]								
∠ 20°	∠ 30°	∠ 45°	∠ 60°	303不锈钢	316不锈钢	黄铜		0.5	1.0	2.0	40* psi			3.0	5.0	7.0
664.721	664.722	664.723	664.724	○	○	○	2.1-2.5	3.15	4.45	6.30	1.95	7.72	9.96	11.79	14.09	
664.761	664.762	664.763	664.764	○	○	○	2.3-2.8	4.00	5.66	8.00	2.48	9.80	12.65	14.97	17.89	
664.801	664.802	664.803	664.804	○	○	○	2.6-3.2	5.00	7.07	10.00	3.10	12.25	15.81	18.71	22.36	
664.841	664.842	664.843	664.844	○	○	○	3.0-3.6	6.25	8.84	12.50	3.88	15.31	19.76	23.39	27.95	
664.881	664.882	664.883	664.884	○	○	○	3.4-4.0	8.00	11.31	16.00	4.96	19.60	25.30	29.93	35.78	
664.821	664.922	664.923	664.924	○	○	○	4.1-4.4	10.00	14.14	20.00	6.20	24.49	31.62	37.42	44.72	
664.961	664.962	664.963	664.964	○	○	○	4.2-5.3	12.50	17.68	25.00	7.75	30.62	39.53	46.77	55.90	
-	-	664.983	-	○	○	○	4.7	14.00	19.80	28.00	8.68	34.29	44.27	52.38	62.61	
-	-	665.013	-	○	○	○	5.2	16.75	23.69	33.50	10.40	41.03	52.97	62.67	74.91	
665.041	665.042	665.043	665.044	○	○	○	5.5-6.6	20.00	28.28	40.00	12.41	48.99	63.25	74.83	89.44	
-	-	-	665.084	○	○	○	6.2	25.00	35.36	50.00	15.50	61.24	79.06	93.54	111.80	
665.121	665.122	665.123	665.124	○	○	○	7.4-8.3	31.50	44.55	63.00	19.56	77.16	99.61	117.86	140.87	
-	665.202	-	-	○	○	○	10.5	50.00	70.71	100.00	31.04	127.47	158.11	187.08	223.61	

E= 最窄断面。 *美制加仑/分

注: 参数可随时因技术改进而略有调整

配件

重量: 65 g

焊座, 066.410.17 (1.4571)
066.410.03 (St52-3)

重量 60 g

螺帽, 065.600.16(1.4305)
065.600.17(1.4571)
065.600.30(黄铜)

其它偏转角度可订制

