



喷射宽度 [B] p=3 bar

	H 250 mm	H 500 mm
660.301 - 331	70	125
660.361 - 761	90	175
660.801 - 881	100	200
660.302 - 332	110	210
660.362 - 402	135	260
660.442 - 882	150	300
660.303 - 333	175	350
660.363 - 403	200	400
660.443 - 923	220	440
660.304 - 334	250	470
660.364 - 404	315	600
660.444 - 924	330	630



订货号				材料号			E $\phi$ [mm]	$\dot{V}$ [l/min]							
型号				16 303不锈钢	17 316不锈钢	30 铜		p [bar]							
$\angle 20^\circ$	$\angle 30^\circ$	$\angle 45^\circ$	$\angle 60^\circ$					40* psi							
660.301	660.302	660.303	660.304	○	-	○	0.4-0.6	0.16	0.23	0.32	0.10	0.39	0.50	0.59	0.71
660.331	660.332	660.333	660.334	○	-	○	0.5-0.7	0.22	0.32	0.45	0.14	0.55	0.71	0.84	1.00
660.361	660.362	660.363	660.364	○	○	○	0.6-0.8	0.31	0.44	0.63	0.20	0.77	0.99	1.17	1.40
660.401	660.402	660.403	660.404	○	○	○	0.8-1.0	0.50	0.70	1.00	0.31	1.22	1.58	1.87	2.23
660.441	660.442	660.443	660.444	○	○	○	0.9-1.1	0.62	0.88	1.25	0.39	1.53	1.97	2.33	2.79
660.481	660.482	660.483	660.484	○	○	○	1.0-1.2	0.80	1.13	1.60	0.50	1.96	2.53	2.99	3.57
660.511	660.512	660.513	660.514	○	○	○	1.1-1.4	0.95	1.34	1.90	0.59	2.32	3.00	3.55	4.24
660.561	660.562	660.563	660.564	○	○	○	1.3-1.5	1.25	1.76	2.50	0.78	3.06	3.95	4.67	5.59
660.601	660.602	660.603	660.604	○	○	○	1.5-1.7	1.57	2.22	3.15	0.98	3.85	4.98	5.89	7.04
660.641	660.642	660.643	660.644	○	○	○	1.6-1.9	2.00	2.82	4.00	1.24	4.89	6.32	7.48	8.94
660.671	660.672	660.673	660.674	○	○	○	1.8-2.2	2.37	3.35	4.75	1.47	5.81	7.51	8.88	10.62
660.721	660.722	660.723	660.724	○	○	○	2.1-2.5	3.15	4.45	6.30	1.95	7.71	9.96	11.78	14.08
660.761	660.762	660.763	660.764	○	○	○	2.3-2.8	4.00	5.65	8.00	2.48	9.79	12.64	14.96	17.88
660.801	660.802	660.803	660.804	○	○	○	2.6-3.2	5.00	7.07	10.00	3.10	12.24	15.81	18.70	22.36
660.841	660.842	660.843	660.844	○	○	○	3.0-3.6	6.25	8.83	12.50	3.88	15.30	19.76	23.38	27.95
660.881	660.882	660.883	660.884	○	○	○	3.4-4.0	8.00	11.31	16.00	4.96	19.53	25.29	29.93	35.77
-	-	660.923	660.924	○	○	○	4.1-4.4	10.00	14.14	20.00	6.21	24.49	31.62	37.42	44.72

E= 最窄断面。 \*美制加仑/分

注: 参数可随时因技术改进而略有调整

配件

